



0.028.883/8

## ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.288.837/8	Full Suspension	27,5"	40	blue / black	12
0.288.838/6	Full Suspension	27,5"	43	blue / black	12
0.288.839/4	Full Suspension	27,5"	46	blue / black	12
0.288.840/2	Full Suspension	27,5"	49	blue / black	12

## E-BIKE INFO

bis 25 km/h Mittelmotor W Wh

## WEITERE AUSFÜHRUNGEN



0.288.838/6

## AUSSTATTUNGLISTE

Rahmen	CONWAY Fully Intube Bosch, Alu
Schalttauge	0281180/0
Gabel	FOX "Performance 36 Float", 150 mm
Steuersatz	ZS44 / ZS56
Kurbelarme	MIRANDA "Epsilon", 165 mm
Kettenblatt/Riemenscheibe	MIRANDA B 36 Z.
Innenlager	BOSCH
Bremse	MAGURA "MT5 eStop"
Bremshebel	MAGURA "MT5 eStop"
Bremsscheibe V.R.	MAGURA "MDR-P", 203 mm
Bremsscheibe H.R.	MAGURA "MDR-P", 203 mm
Schalthebel	SHIMANO "Deore XT SL-M8100"
Schaltwerk	SHIMANO "Deore XT RD-M8100", Shadow Plus, 12speed
Zahnkranz/Riemenscheibe	SHIMANO "CS-M7100", 10-51 Z.
Kette/Riemen	SHIMANO "CN-M6100"
Motor	BOSCH Mittelmotor Gen.4 "Performance CX", 36 V, 250 W
Akku	BOSCH PT Lithium-Ionen mit BMS, 36 V, 16,66 Ah, 625 Wh
Ladegerät	Bosch 4 Ah
Display	BOSCH, "Kiox", 4-Stufen, Remote Control, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	DT SWISS "Spline H1900"
Speichen	DT SWISS
Nabe V.R.	DT SWISS „Spline H1900“, 15 x 110 mm
Nabe H.R.	DT SWISS „Spline H1900“, 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Soft, 65-584
Reifen H.R.	SCHWALBE "Hans Dampf", Spgrip, 65-584
Lenker	CONWAY "Low Rizer", Ø 35, 780 mm
Lenkervorbau	CONWAY, 35 mm
Lenkergriff	CONWAY "Sport fix"
Sattel	FIZIK "Aidon", Regular 145
Sattelstütze	CONTEC "Drop - A - Gogo", 31,6 mm