



0.028.888/2

ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.288.881/6	Full Suspension	29"	41	pearl white / copper	12
0.288.882/4	Full Suspension	29"	44	pearl white / copper	12
0.288.883/2	Full Suspension	29"	47	pearl white / copper	12
0.288.884/0	Full Suspension	29"	50	pearl white / copper	12

E-BIKE INFO

bis 25 km/h Mittelmotor W Wh

AUSSTATTUNGLISTE

Rahmen	CONWAY Fully Intube Shimano, Alu
Schalttauge	0347028/3
Gabel	FOX "Performance 36 Float", 160 mm
Steuersatz	ZS44 / ZS56, Blocklock
Kurbelarme	SHIMANO "FC-M8150", 165 mm
Kettenblatt/Riemenscheibe	SHIMANO "SM-CRE80 12 B", 34 Z.
Innenlager	SHIMANO
Bremse	SHIMANO "Deore XT BR-M8120", 4-Kolben
Bremshebel	SHIMANO "Deore XT BL-M8100"
Bremsscheibe V.R.	SHIMANO "RT-MT800", 203 mm
Bremsscheibe H.R.	SHIMANO "RT-EM800", Magnet, 203 mm
Schalthebel	SHIMANO "Deore XT SL-M8100"
Schaltwerk	SHIMANO "Deore XT RD-M8100", Shadow Plus, 12speed
Zahnkranz/Riemenscheibe	SHIMANO "CS-M7100", 10-51 Z.
Kette/Riemen	SHIMANO "CN-M6100"
Motor	SHIMANO Mittelmotor "NEW", 250 W Nenn-Dauerleistung
Akku	SHIMANO Lithium-Ionen mit BMS, 36 V, 17,5 Ah, 630 Wh
Ladegerät	Shimano 4 Ah
Display	SHIMANO, "SC-EM800" 3-Stufen, Remote Control, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	DT SWISS „Spline H1900"
Speichen	DT SWISS
Nabe V.R.	DT SWISS „Spline H1900", 15 x 110 mm
Nabe H.R.	DT SWISS „Spline H1900", 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Soft, 60-622
Reifen H.R.	SCHWALBE "Hans Dampf", Soft, 60-622
Lenker	RACEFACE "Aeffect R", Ø 35, 780 mm
Lenkervorbau	RACEFACE "Aeffect R", 35 mm
Lenkergriff	RACEFACE "Half Nelson"
Sattel	FIZIK "Aidon", Regular 145
Sattelstütze	CONTEC "Drop - A - Gogo", 31,6 mm