

625 Wh 25 km/h 250 W

Motor 6 km/h



0.287.976/5

## ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.287.975/7	Herren	27,5"	S	red / black matt	12
0.287.976/5	Herren	27,5"	M	red / black matt	12
0.287.977/3	Herren	27,5"	L	red / black matt	12
0.287.978/1	Herren	27,5"	XL	red / black matt	12
0.287.979/9	Herren	27,5"	S	grey matt / black matt	12
0.287.980/7	Herren	27,5"	M	grey matt / black matt	12
0.287.981/5	Herren	27,5"	L	grey matt / black matt	12
0.287.982/3	Herren	27,5"	XL	grey matt / black matt	12

## WEITERE AUSFÜHRUNGEN



0.287.980/7



0.287.980/7

## AUSSTATTUNGSLISTE

Rahmen	CONWAY Fully, Carbon
Gabel	FOX "Performance 36 Float", 140 mm
Kettenradgarnitur	FSA "E-MTB Bosch", 38 Z.
Innenlager	BOSCH
Bremse	SHIMANO "BR-MT520", 4-Kolben, 203 mm
Bremshebel	SHIMANO "BL-MT501"
Schalthebel	SRAM "SX Eagle Trigger"
Schaltwerk	SRAM "NX Eagle", 12-fach
Kassette/Ritzelpaket	SRAM "PG 1230 Eagle", 11-50 Z.
Kette/Riemen	SRAM "SX Eagle"
Motor	BOSCH Mittelmotor Gen.4 "Performance CX", 36 V, 250 W
Akku	BOSCH PT Lithium-Ionen mit BMS, 36 V, 16,66 Ah, 625 Wh
Ladegerät	Bosch 4 Ah
Display	BOSCH "Purion" 4-Stufen, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	RODI "Ready 35"
Speichen	Niro
Nabe V.R.	FORMULA "DC 711", 15 x 110 mm
Nabe H.R.	FORMULA "eHL-148 S", 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Snksk
Reifen H.R.	"Hans Dampf", Spgrip, 65-584
Lenker	CONWAY "Low Rizer", Ø 35 mm, 780 mm
Lenkervorbau	CONWAY, 35 mm
Lenkergriff	CONWAY "Sport fix"
Sattel	CONWAY "1489 sport light"
Sattelstütze	CONTEC "Drop - A - Gogo", 31,6 mm