

 500 Wh
  25 km/h
  250 W

 Motor
  6 km/h



0.287.440/2

ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.287.439/4	Herren	29"	S	black stealth	12
0.287.440/2	Herren	29"	M	black stealth	12
0.287.441/0	Herren	29"	L	black stealth	12
0.287.442/8	Herren	29"	XL	black stealth	12

WEITERE AUSFÜHRUNGEN



0.287.440/2



0.287.440/2

AUSSTATTUNGLISTE

Rahmen	CONWAY Fully E8000, Alu
Schaltauge	0.280.931/7
Gabel	ROCKSHOX "Pike RC Air", 140 mm
Kettenradgarnitur	SHIMANO "FC-E8000", 34 Z., 165 mm
Innenlager	SHIMANO
Bremse	SHIMANO "XTR BR-M9020", 4-Kolben, 203 mm
Bremshebel	SHIMANO "XTR"
Schalthebel	SHIMANO "XTR SL-M9100"
Schaltwerk	SHIMANO "XTR RD-M9100 Shadow Plus", 12-fach
Kassette/Ritzelpaket	SHIMANO "XTR CS-M9100", 10-51 Z.
Kette/Riemen	SHIMANO "XTR CN-9100"
Motor	SHIMANO Mittelmotor "E8000", 250 W
Akku	SHIMANO Lithium-Ionen mit BMS, 36 V, 14 Ah, 504 Wh
Ladegerät	SHIMANO, 4 Ah
Display	SHIMANO "SCE800", 3-Stufen, Remote Control, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	DT SWISS "Spline HX 1501"
Speichen	DT SWISS
Nabe V.R.	DT SWISS "Spline HX 1501", 29", 15 x 110 mm
Nabe H.R.	DT SWISS "Spline HX 1501", 29", 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Apex
Reifen H.R.	SCHWALBE "Hans Dampf", SuperG, 60-622
Lenker	CONWAY "Low Rizer", Ø 35 mm, 780 mm
Lenkervorbau	CONWAY, 35 mm
Lenkergriff	CONWAY "Sport fix"
Sattel	CONWAY "1489 sport light"
Sattelstütze	FOX "Transfer Factory", Ø 30,9 mm
Gewicht	21,4 kg