



0.028.887/4

ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.288.873/3	Full Suspension	29"	41	light grey / acid	11
0.288.874/1	Full Suspension	29"	44	light grey / acid	11
0.288.875/8	Full Suspension	29"	47	light grey / acid	11
0.288.876/6	Full Suspension	29"	50	light grey / acid	11

E-BIKE INFO

bis 25 km/h Mittelmotor W Wh

AUSSTATTUNGLISTE

Rahmen	CONWAY Fully Intube Shimano, Alu
Schaltauge	0347028/3
Gabel	ROCKSHOX "35 Gold RL", 160 mm
Steuersatz	ZS44 / ZS56, Blocklock
Kurbelarme	SHIMANO "FC-EM600", 165 mm
Kettenblatt/Riemenscheibe	SHIMANO "SM-CRE80 12 B", 34 Z.
Innenlager	SHIMANO
Bremse	SHIMANO "BR-MT420", 4-Kolben
Bremshebel	SHIMANO "BL-M4100"
Bremsscheibe V.R.	SHIMANO "SM-RT64", 203 mm
Bremsscheibe H.R.	SHIMANO "RT-EM600", Magnet, 203 mm
Schalthebel	SHIMANO "Deore SL-M5100"
Schaltwerk	SHIMANO "Deore RD-M5100 Shadow Plus", 11speed
Zahnkranz/Riemenscheibe	SHIMANO "CS-M5100", 11-51 Z.
Kette/Riemen	SHIMANO "CN-M6011"
Motor	SHIMANO Mittelmotor "NEW", 250 W Nenn-Dauerleistung
Akku	SHIMANO Lithium-Ionen mit BMS, 36 V, 17,5 Ah, 630 Wh
Ladegerät	Shimano 4 Ah
Display	SHIMANO, "SC-EM800" 3-Stufen, Remote Control, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	RODI "Ready 35"
Speichen	Niro
Nabe V.R.	SHIMANO "HB-MT400", 15 x 110 mm
Nabe H.R.	SHIMANO "FH-MT400B", 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Soft, 60-622
Reifen H.R.	SCHWALBE "Hans Dampf", Soft, 60-622
Lenker	CONWAY "Low Rizer", Ø 35, 780 mm
Lenkervorbau	CONWAY, 35 mm
Lenkergriff	CONWAY "Sport fix"
Sattel	FIZIK "Aidon", Regular 145
Sattelstütze	CONTEC "Drop - A - Gogo", 31,6 mm