



0.028.888/6

## ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.288.885/7	Full Suspension	29"	41	darkblue metallic / acid	12
0.288.886/5	Full Suspension	29"	44	darkblue metallic / acid	12
0.288.887/3	Full Suspension	29"	47	darkblue metallic / acid	12
0.288.888/1	Full Suspension	29"	50	darkblue metallic / acid	12

## E-BIKE INFO

bis 25 km/h Mittelmotor W Wh

## AUSSTATTUNGLISTE

Rahmen	CONWAY Fully Intube Shimano, Alu
Schalttauge	0347028/3
Gabel	ROCKSHOX "Lyrik Select", 170 mm
Steuersatz	ZS44 / ZS56, Blocklock
Kurbelarme	SHIMANO "FC-EM600", 165 mm
Kettenblatt/Riemenscheibe	SHIMANO "SM-CRE80 12 B", 34 Z.
Innenlager	SHIMANO
Bremse	SHIMANO "SLX BR-M7120", 4-Kolben
Bremshebel	SHIMANO "SLX BL-M7100"
Bremsscheibe V.R.	SHIMANO "SM-RT64", 203 mm
Bremsscheibe H.R.	SHIMANO "RT-EM600", Magnet, 203 mm
Schalthebel	SHIMANO "Deore SL-M6100"
Schaltwerk	SHIMANO "Deore XT RD-M8100", Shadow Plus, 12speed
Zahnkranz/Riemenscheibe	SHIMANO "CS-M6100", 10-51 Z.
Kette/Riemen	SHIMANO "CN-M6100"
Motor	SHIMANO Mittelmotor "NEW", 250 W Nenn-Dauerleistung
Akku	SHIMANO Lithium-Ionen mit BMS, 36 V, 17,5 Ah, 630 Wh
Ladegerät	Shimano 4 Ah
Display	SHIMANO, "SC-EM800" 3-Stufen, Remote Control, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	DT SWISS "Spline H1900 35", 27,5", "Spline H1900 30", 29"
Speichen	DT SWISS
Nabe V.R.	DT SWISS „Spline H1900", 29", 15 x 110 mm
Nabe H.R.	DT SWISS „Spline H1900", 27,5", 12 x 148 mm
Reifen V.R.	SCHWALBE "Magic Mary", Soft, 60-622
Reifen H.R.	SCHWALBE "Hans Dampf", Spgrip, 65-584
Lenker	RACEFACE "Aeffect R", Ø 35, 780 mm
Lenkervorbau	RACEFACE "Aeffect R", 35 mm
Lenkergriff	RACEFACE "Half Nelson"
Sattel	FIZIK "Aidon", Regular 145
Sattelstütze	CONTEC "Drop - A - Gogo", 31,6 mm