



0.028.854/4

ARTIKELGRUPPE

Art.-Nr.	Form	Zoll	RH (cm)	Farbe	Gg.
0.288.543/2	Diamant	27,5"	41	white / red black	9
0.288.544/0	Diamant	27,5"	45	white / red black	9
0.288.545/7	Diamant	27,5"	49	white / red black	9
0.288.546/5	Trapez	27,5"	38	white / red black	9
0.288.547/3	Trapez	27,5"	42	white / red black	9
0.288.548/1	Trapez	27,5"	46	white / red black	9
0.288.549/9	Trapez	27,5"	50	white / red black	9

E-BIKE INFO

bis 25 km/h Mittelmotor W Wh

WEITERE AUSFÜHRUNGEN



0.028.854/7

AUSSTATTUNGLISTE

Rahmen	CONWAY Bosch, Alu
Schaltauge	0281167/7
Gabel	RST "Aerial Air MLO", 120 mm
Steuersatz	ZS44 / ZS56, Reduzierkonus
Kurbelarme	FSA "CK-745", 170 mm
Kettenblatt/Riemenscheibe	FSA "W0146 WB460 W1155", 38 Z.
Innenlager	BOSCH
Bremse	SHIMANO "BR-MT200"
Bremshebel	SHIMANO "BL-MT200"
Bremsscheibe V.R.	SHIMANO "SM-RT30", 180 mm
Bremsscheibe H.R.	SHIMANO "SM-RT30", 180 mm
Schalthebel	SHIMANO "Altus SL-M2000"
Schaltwerk	SHIMANO "Deore RD-M592", 9speed
Zahnkranz/Riemenscheibe	SHIMANO "HG200", 11-36 Z.
Kette/Riemen	SHIMANO "HG53"
Motor	BOSCH Mittelmotor Gen.4 "Performance CX", 36 V, 250 W
Akku	BOSCH Lithium-Ionen mit BMS, 36 V, 13,88 Ah, 5 Wh
Ladegerät	Bosch 2 Ah
Display	BOSCH, "Purion", 4-Stufen, Schiebehilfe
Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
Felgen	CONWAY Hohlkammer "X17", Disc
Speichen	Niro
Nabe V.R.	SHIMANO "HB-TX505" QR
Nabe H.R.	SHIMANO "FH-TX505" QR
Reifen V.R.	IMPAC "Ridgepac", 57-584
Reifen H.R.	IMPAC "Ridgepac", 57-584
Lenker	CONWAY Riser, Ø 31,8, 720 mm
Lenkervorbau	CONWAY, 31,8 mm
Lenkergriff	CONWAY "Sport"
Sattel	SELLE ROYAL "Vivo Athletic Ergo"
Sattelstütze	CONWAY Patent, 31,6 mm
Pedale	VP "VPE-506"